

MB

Earthing tapes



Product description

Manufactured with highly flexible E-Cu stranded wires with connecting end pads made of tinned copper strips.

The minimum transition and connecting resistance makes them perfectly suitable for use as earthing tapes.

Earthing Tapes are available with M6 or M8 connections and in some sizes with both connections combined.

| Type | Order No. | Length L [mm] | Cross-section mm ² | Hole size | PU |
|-----------------|-----------|------------------|----------------------------------|-----------|----|
| MB 100 6 M6 | 32700 | 100 | 6 | M6 | 1 |
| MB 150 6 M6 | 32701 | 150 | 6 | M6 | 1 |
| MB 200 6 M6 | 32702 | 200 | 6 | M6 | 1 |
| MB 300 6 M6 | 32703 | 300 | 6 | M6 | 1 |
| MB 400 6 M6 | 32704 | 400 | 6 | M6 | 1 |
| MB 500 6 M6 | 32705 | 500 | 6 | M6 | 1 |
| MB 100 10 M6 | 32730 | 100 | 10 | M6 | 1 |
| MB 100 10 M8 | 32731 | 100 | 10 | M8 | 1 |
| MB 150 10 M8 | 32732 | 150 | 10 | M8 | 1 |
| MB 200 10 M6 | 32733 | 200 | 10 | M6 | 1 |
| MB 200 10 M8 | 32734 | 200 | 10 | M8 | 1 |
| MB 200 10 M6+M8 | 32741 | 200 | 10 | M6 + M8 | 1 |
| MB 250 10 M6+M8 | 32742 | 250 | 10 | M6 + M8 | 1 |
| MB 300 10 M6 | 32735 | 300 | 10 | M6 | 1 |
| MB 300 10 M8 | 32736 | 300 | 10 | M8 | 1 |
| MB 300 10 M6+M8 | 32743 | 300 | 10 | M6 + M8 | 1 |
| MB 400 10 M6 | 32737 | 400 | 10 | M6 | 1 |
| MB 400 10 M8 | 32738 | 400 | 10 | M8 | 1 |
| MB 500 10 M6 | 32739 | 500 | 10 | M6 | 1 |
| MB 100 16 M6 | 32760 | 100 | 16 | M6 | 1 |
| MB 100 16 M8 | 32761 | 100 | 16 | M8 | 1 |
| MB 150 16 M6 | 32762 | 150 | 16 | M6 | 1 |
| MB 150 16 M8 | 32763 | 150 | 16 | M8 | 1 |
| MB 200 16 M6 | 32764 | 200 | 16 | M6 | 1 |
| MB 200 16 M8 | 32765 | 200 | 16 | M8 | 1 |

MB Earthing tapes



Connecting end pads (copper)



| Type | Order No. | Length L [mm] | Cross-section mm ² | Hole size | PU |
|-----------------|-----------|------------------|----------------------------------|-----------|----|
| MB 200 16 M6+M8 | 32773 | 200 | 16 | M6 + M8 | 1 |
| MB 250 16 M8 | 32766 | 250 | 16 | M8 | 1 |
| MB 250 16 M6+M8 | 32774 | 250 | 16 | M6+M8 | 1 |
| MB 300 16 M6 | 32767 | 300 | 16 | M6 | 1 |
| MB 300 16 M8 | 32768 | 300 | 16 | M8 | 1 |
| MB 300 16 M6+8 | 32775 | 300 | 16 | M6+M8 | 1 |
| MB 350 16 M8 | 32769 | 350 | 16 | M8 | 1 |
| MB 400 16 M8 | 32770 | 400 | 16 | M8 | 1 |
| MB 500 16 M8 | 32771 | 500 | 16 | M8 | 1 |
| MB 600 16 M8 | 32772 | 600 | 16 | M8 | 1 |
| MB 100 25 M10 | 32800 | 100 | 25 | M10 | 1 |
| MB 150 25 M10 | 32801 | 150 | 25 | M10 | 1 |
| MB 200 25 M8 | 32802 | 200 | 25 | M8 | 1 |
| MB 200 25 M10 | 32803 | 200 | 25 | M10 | 1 |
| MB 250 25 M8 | 32804 | 250 | 25 | M8 | 1 |
| MB 250 25 M10 | 32805 | 250 | 25 | M10 | 1 |
| MB 300 25 M8 | 32806 | 300 | 25 | M8 | 1 |
| MB 300 25 M10 | 32807 | 300 | 25 | M10 | 1 |
| MB 350 25 M10 | 32808 | 350 | 25 | M10 | 1 |
| MB 400 25 M8 | 32809 | 400 | 25 | M8 | 1 |
| MB 500 25 M8 | 32810 | 500 | 25 | M8 | 1 |
| MB 600 25 M8 | 32811 | 600 | 25 | M8 | 1 |

Advantages

- Available in various lengths and cross-sections
- Cost-effective
- Low transition impedances

Specification

Material Cu-ETP with connecting end pads
Pads made of tinned copper strips

