

SF|ZL

Strain Relief Plates for 35 mm DIN Rail



Type	Order No.	Length L1	Length L2	No. of teeth	PU
SF ZL 39	32351	38.5 mm	19.5 mm	3	10
SF ZL 60	32352	59.5 mm	43.5 mm	4	10
SF ZL 70	32353	69.1 mm	43.5 mm	5	10
SF ZL 87	32354	86.5 mm	68 mm	6	10
SF ZL 103	32355	102.5 mm	84 mm	7	10
SF ZL 121	32356	121 mm	102.5 mm	8	10
SF ZL 140	32357	139.5 mm	121 mm	9	10
SF ZL 180	32358	180 mm	157 mm	12	10

Product Description

The strain relief plate SF|ZL is used for assembly on 35 mm DIN rails shape H. It can be used for strain relief of cables and conduits.

The SF|ZL range is based upon the strain relief plate ZL, which is mounted on snap feet for 35 mm DIN rails shape H.

Advantages

- Simple assembly
- Cost-effective
- High packing density
- Universal usage

Specifications

Material	ZL: Polyamide (PA) SF-foot: Spring steel
Flame class	UL94-Vo, self-extinguishing
Temperature	- 40°C to + 140°C (static)
Properties	Halogen free, silicone free

Accessories

KB Cable ties Page 145