

SFZ|SKL

EMC Shield Clamps for 35 mm DIN Rail



Product Description

The shield clamps SFZ|SKL are used for shielding single cables in combination with strain relief. Easy to use and effective in shielding of cables.

Cables are secured with a cable tie. Strain relief in accordance with EN 50262 is achieved.

For assembly on 35 mm DIN rails.

Advantages

- Simple and tool-free assembly
- Vibration proof, maintenance free
- Strain relief of the cable and shielding in a single device
- Optimal contact of the cable shield
- Permanent and continuous spring pressure on the cable shield, no adjustment of the spring load required

Specifications

Material

SKL-clamp Spring steel, zinc plated
SF- / SFZ-foot Spring steel

Accessories

KB Cable ties Page 145
Stripping tool Page 103

Type	Order No.	Shield diameter	PU
SFZ SKL 1.5-3	36850	1.5 - 3 mm	10
SFZ SKL 3-6	36855	3 - 6 mm	10
SFZ SKL 6-8	36860	6 - 8 mm	10
SFZ SKL 8-11	36865	8 - 11 mm	10
SFZ SKL 12-16	36870	12 - 16 mm	10
SFZ SKL 17-22	36875	17 - 22 mm	10
SFZ SKL 23-29	36880	23 - 29 mm	10

SF|SKL EMC Shield Clamps for 35 mm DIN Rail



Type	Order No.	Shield diameter	PU
SF SKL 1.5-3	36243	1.5 - 3 mm	10
SF SKL 3-6	36244	3 - 6 mm	10
SF SKL 6-8	36245	6 - 8 mm	10
SF SKL 8-11	36246	8 - 11 mm	10
SF SKL 12-16	36247	12 - 16 mm	10
SF SKL 17-22	36248	17 - 22 mm	10
SF SKL 23-29	36249	23 - 29 mm	10
SF SKL 30-37	36250	30 - 37 mm	10
SF SKL 38-48	36252	38 - 48 mm	10
SF single	36230	Snap foot single	10

Product Description

The shield clamps SF|SKL are used for shielding single cables.

Simple to use and effective in shielding of cables.

For assembly on 35 mm DIN rails.

Advantages

- Optimal contact of the cable shield
- Simple and tool-free assembly
- Permanent and continuous spring pressure on the cable shield, no adjustment of the spring load required
- Space saving by an optimized arrangement
- Vibration proof, maintenance free

Specifications

Material
SKL-clamp Spring steel, zinc plated
SF-foot Spring steel

Accessories

Stripping tool Page 103

SFS|SKL

EMC Shield Clamps for 35 mm DIN Rail



Product Description

Comparable with type SF|SKL, the SFS|SKL shield clamps are easily mounted on 35 mm DIN-rails.

The staggered arrangement of SFS|SKL provides optimal space utilization. Suitable for applications when there is a need for mounting cables in direct proximity.

Advantages

- High packing density
- Simple and tool-free assembly
- Permanent and continuous pressure on the cable shield, no adjustment of the spring load required
- Optimal contact of the cable shield
- Vibration proof, maintenance free

Specifications

Material
SKL-clamp Spring steel, zinc plated
SFS-foot Spring steel

Accessories

Stripping tool Page 103

Type	Order No.	Shield diameter	PU
SFS SKL 1.5-3	36810	1.5 - 3 mm	10
SFS SKL 3-6	36815	3 - 6 mm	10
SFS SKL 6-8	36820	6 - 8 mm	10
SFS single	36229	Snap foot single	10